## FR MINI 50 x 70



bread-making and confectionery Laboratories. Available with 8 or 10 type of product, even the most hydrated. Extremely versatile. Its baking trays (40x60 cm or 50x70 cm), in the electrical or with burner (Gas multiple configuration options and reduced dimensions make it or diesel) version. Façade and baking chamber made of stainless steel. suitable for many requirements. Ideal as a baking point for shopping Double glass door. Manual or motorised steam exhaust valve. Powerful, centres, hotels and restaurants. removable, and easy to clean steamer. Crossed rockwool panel insulation. The oven is provided with proofer of 16 trays for the electrical High performance armoured heating elements inserted from the top or version, 10 trays for burner type. It is available with front burner.

Hot air circulates evenly in every point of the baking chamber.

Fr mini is a rotary convection oven for reduced loads. Recommended for A suitable amount of highquality steam allows the baking of any

electromechanical or digital control panel. Three phase power supply 230v or 400v. 50 or 60 hz. Special voltage upon request.











FR mini gas or diesel





MODEL	TRAY	DISTAI	NCE	BAKING	DIMENSIONS	POWER			WEIGHT
ELECTRIC	СМ	NR	MM	MQ	MM - W x L x H + H1	KW	KW	KCAL	KG
FR MINI E57.8	50 x 70	8	83	2.8	1070 x 1200 x 1110 + 200	1.5	12.0		335
FR MINI E57.10	50 x 70	10	83	3.5	1070 x 1200 x 1280 + 200	1.5	12.0		350
FR MINI E57.PR	50 x 70	16	93		1070 x 1200 x 855	0.5			80
FR MINI E57.ST	50 x 70	12	82		1070 x 1200 x 673				35
MODEL	TRAY	DISTANCE		BAKING	DIMENSIONS	POWER		WEIGHT	
GAS/DIESEL	СМ	NR	MM	MQ	MM - W x L x H + H1	KW	KW	KCAL	KG
FR MINI 57.8	50 x 70	8	83	2.8	1070 x 1200 x 1110 + 200	1.5		20.000	470
FR MINI 57.10	50 x 70	10	83	3.5	1070 x 1200 x 1280 + 200	1.5		20.000	490
PROOFER	50 x 70	10	80		1070 x 1200 x 930	0.5			180